

CUSTOM[®]

Very fast:
140mm/sec

Small Size



Nice Design

Easy Loading

Reliable

Thermal Desktop Printers

Neo's

Neo's

High performance thermal desktop printer for paper width 60mm and high printing speed up to 140mm/sec. Small and reliable, neo's is suitable as kitchen printer, for coupons, receipts or invoices printing and connected to POS cash systems; the printer is the right solution for measurement and control instruments and medical equipments.

Neo's PS with internal power supply. Easier paper loading thanks to the access from front and to autoloading system.

Optional cutter (total and partial cut).
Interfaces: RS232 and RS485.

All models are available with cash drawer control and drivers (Windows and Linux) and software tools to create and update logos and fonts.

Most common barcodes printing: UPC-A, UPC-E, EAN 13, EAN 8, CODE 39, ITF, CODABAR, CODE 128, CODE 32 PHARMACEUTICAL, CODE 93.

Double colour printing (red/black - blue/black).

Neo's PS USB model with USB interface is also available.

Neo's PS RF neo's printer with internal power supply for receipts and invoices. This model allows the ticket alignment thanks to additional commands on printer firmware.

Neo's 24 with 24Vdc external power supply (optional).
Available interfaces for this model are serial RS232 or parallel Centronics.



Neo's
Fast and Small



Neo's PS

Neo's PS USB

Neo's 24

| | | | |
|-----------------------|---|------|--|
| Printing Method | Thermal fixed head (8 dot/mm) | | |
| Resolution | 203 dpi | | |
| Printing Speed (mm/s) | Low >110 Normal >140 | | |
| Character Set | ASCII standard, International | | |
| Type Styles | Normal, double and quadruple height and width, reverse, underscored, italic, bold | | |
| Printing Direction | Straight, 180° | | Straight, 90°, 180°, 270° |
| Paper Width | 60 ± 0.5 mm | | |
| Roll Dimension | max 65 mm | | |
| Emulation | ESC/POST™ | | |
| Interface | RS232, RS485 | USB | RS232, Centronics |
| Baud Rate | From 1.200 to 57.600 bps | none | From 1.200 to 57.600 bps |
| Data Buffer | 8 Kb | | |
| Flash Memory | 256 Kb | | |
| Graphic Memory | 3 logos of 32 Kb | | |
| Drivers | Windows™ 95, 98, me, NT4, 2K, XP; Linux | | |
| Software Tools | Logo Editor, Font Editor | | |
| Power Consumption | 1 A | | |
| Power | 90-240 Vac, 50/60 Hz | | 24 Vdc ± 10% (optional external power supply) |
| DKD Function | 1 driver | | |
| MTBF | 300.000 hours | | |
| Safety | EN60950 +A1 +A2 +A3 +A4 | | |
| Dimension (LxWxH) | 170x120x100 mm (h=110mm with cutter) | | |
| Options | Partial Cut | | |



Very fast
140mm/sec

CUSTOM[®]

CUSTOM ENGINEERING SPA

Via Berettine, 2 - 43010 Fontevivo, Parma ITALY
Tel. +39 0521 680111 - Fax +39 0521 610701
info@custom.biz - www.custom.biz



M. U. R. S. T.
Ministry University
Research Scientific
Technology
Authorized laboratory
n o . 5 0 8 4 6 2 Y Z

POS Solutions



CUSTOM ENGINEERING MILAN
Via Pavia, 10 - 20053 Muggiò, Milano ITALY
Tel. +39 039 2144280 - Fax +39 039 2144249
custom.milano@custom.it

CUSTOM ENGINEERING MODENA
V.le Virgilio, 56D - 41010 Modena ITALY
Tel. +39 059 8869511 - Fax +39 059 8869512
custom.modena@custom.it

CUSTOM ENGINEERING UK LTD
31 Scott Road, Sundon Park
Luton LU3 3BF UK
Tel +44 (0) 1582 582258 - Fax +44 (0) 1582 564888
uk.sales@custom.it

CUSTOM ENGINEERING IBERIAN
Calle Azagador de Alboraya, 14 P.ta 16
46020 Valencia SPAIN
Tel. +34 96 3627315 - Fax +34 96 3627315
es.ventas@custom.it

CUSTOM ENGINEERING USA
3104 N. Arlington Heights Rd.
Arlington Heights, IL 60004
Tel. +1 (847) 818-1260 - Fax +1 (847) 818-1287
us.sales@custom.it